

Mobile stages

Stagemobil S

Stage floor

Width x Depth	4.40m x 3.75m
Surface	16.5m ²
Floor height	≈ 0.8m
Resistance	300kg/m ²

Roof

Width x Depth	4.40m x 3.75m
Capacity	400kg
Clearance	3.6m

Setup

Stage technician	1 person
Estimated setup	1-2 hours

Stagemobil L

Stage floor

Width x Depth	6.80m x 6.30m
Surface	42m ²
Floor height	≈ 1.0m – 1.2m
Resistance	300kg/m ²

Roof

Width x Depth	6.80m x 4.40m
Capacity	200kg
Clearance	3.5m
Optional sound wing	2 x 300kg

Setup

Stage technician	1 person
Stage hands	1 person
Estimated setup	1-2 hours

Stagemobil XLR

Stage floor

Width x Depth	9.0m x 6.1m
Surface	55m ²
Floor height	≈ 1.1m – 1.3m
Resistance	300kg/m ²

Roof

Width x Depth	9.0m x 6.1m
Capacity	880kg
Clearance	3.8m – 4.6m
Optional sound wing	2 x 500kg

Setup

Stage technician	1 person
Stage hands	2 persons
Estimated setup	1-2 hours

Stagemobil XXL

Stage floor

Width x Depth	10.00m x 6.10m
Surface	61m ²
Floor height	≈ 1.1m – 1.3m
Resistance	300kg/m ²

Roof

Width x Depth	10.0m x 6.1m
Capacity	900kg
Clearance	4.0m – 4.6m
Optional sound wings	2 x 270/500kg

Setup

Stage technician	1 person
Stage hands	2 persons
Estimated setup	1-2 hours

Mobile stages

Alphastage 160

Stage floor

Width x Depth	13.20m x 11.20m
Surface	147m ²
Floor height	≈ 1.5m – 1.95m
Resistance	500kg/m ²

Roof

Width x Depth	13.60m x 11.50m
Capacity	10.5t equally spread
Clearance	8.0m
Sound wing	2 x 1.5t

Setup

Stage technician	2 persons
Stage hands	4 persons
Estimated setup	4-6 hours

Side production area (per side)

Specifications

Width x Depth	10.00m x 5.00m
Surface	50m ²
Floor height	Follows main stage
Resistance	500kg/m ²

Roof

Clearance front	3.00m
-----------------	-------

Setup

Estimated setup in addition to main stage	+4 hours
---	----------

Back production area

Specifications

Width x Depth	4.00m x 24.00m
Surface	96m ²
Floor height	Follows main stage
Resistance	500kg/m ²

Roof

Clearance front	3.00m
-----------------	-------

Setup

Estimated setup in addition to main stage	+8 hours
---	----------

Stage floor

Nivtec

Brand	Nivtec
Resistance	750kg/m ²

Primarily for indoor use and on flat foundation. Nivtec modules comes in a variety of shapes and sizes and can be built after your needs. Good solutions for stairs and railings.

Layher

Brand	Layher
Resistance	500kg/m ²

Works great for both in- and outdoor builds. The systems is very flexible when it comes to varying foundation. Good solutions for stairs and railings.

FOH solutions

FOH HOF

Floor

Width x Depth	4.00m x 4.00m
Surface	16m ²
Floor height	0.2m – 1.0m
Resistance	750kg/m ²

Roof

Height	3.32m
Clearance	2.46m
Capacity	No load in roof

Other

Weight	150kg
--------	-------

Setup

Stage hands	2 persons
Estimated setup	30 mins
